



## KEMCO Coloured quartz

### Application area

---

- Combined with the COETRANS 1-K Binder or KEMCO QB1 Binder can be used as decorative floor coverings in the outdoor and indoor areas
- Can be used as decorative spreading in various coating systems if a transparent final coating or final sealing is created.

### Features

---

- Grain-size distribution 0.7 - 1.2 mm
- round grained

### Pack size:

---

25 kg bag

### Storage

---

Store in closed original containers in dry rooms at temperatures between +5°C and +25°C.

### Material consumption:

---

- at least 4 kg/m<sup>2</sup> (spreading in)
- at least 7 kg/m<sup>2</sup> (coverings applied with the spatula)

### Colors

---

- yellow / white / black
- red / white / black
- gray / white / black
- umbra
- gray / white / red
- graphite / oxide / ivory
- ocher
- graphite
- agate
- papyrus

### Properties

---

Density approx. g/cm<sup>3</sup>

\* Values obtained at a temperature of 23 °C - 50% rel. humidity. These values vary depending on the weather conditions, such as wind, humidity and temperature.

### Application

---

#### Preparing the substrate

During application, the surface temperature must be 3K above the dew point. If the temperature falls below the dew point during application, moisture which can negatively affect adhesion may form on the surface (DIN 4108 - 5 Tab. 1).

Use only for substrate temperatures and ambient temperatures of at least 10 °C to max. 30 °C and <80% rel. humidity.

For the KEMCO Colorit quartz filling in outdoor areas, an adhesive layer made of COETRANS 1-K Binder must be present.

For the KEMCO Colorit quartz filling in indoor areas, **no** adhesive layer made of KEMCO QB1 Binder must be present.

A KEMCO color quartz spreading is carried out in an adhesive layer of the corresponding coating.

More information on substrate preparation and processing can be found in the separate technical data sheets and the corresponding processing instructions.

To avoid colour variations or shading over the surface, material from different bags must be mixed in advance.

### Important note

---

Please refer to the respective safety data sheet for hazard warnings, protective measures, hazardous substance classes and correct disposal!

### Disposal

---

cured EAK 17 02 03

### General information

---

Our technical data sheets / technical information and application instructions reflect the current level of knowledge in our company and the experience with our products. In each case, the new edition supersedes the previous technical information and renders it invalid. It is therefore necessary that you always have to hand the current code of practise. The latest version can be retrieved from the KEMPER SYSTEM Login section. When using our products, a detailed, object-related and qualified inspection is required in each individual case in order to determine whether the product and /or application technology in question meets the specific requirements and purposes. We are liable only for our products being free from faults, and this only if our relevant product has been used and applied according to the instructions in our technical data sheets. Correct application of our products therefore falls entirely within the scope of liability and responsibility of the user (contractor). Our products are sold exclusively on the bases of our conditions of sale and delivery.

Issued: Vellmar, 2023-03-30