



KEMCO FL Special Filler

Application area

Issued: Vellmar, 2023-03-30

- Filler for coating systems
- As filling compound in combination with KEMCO POX 2K Primer

Features

- Grading curve 0.1 - 0.5 mm
- Kiln-dried

Pack sizes

7.5 kg container

Storage

Cool and dry.

Store in closed original containers in dry rooms at temperatures between +5°C and +25°C.

Consumption

Depending on requirements and field of application.

For further information on application, please refer to the separate technical data sheets and the application instructions.

Disposal

EAK 17 05 04

General information

The times given above are reduced with higher and increased with lower ambient and substrate temperatures. KEMPER SYSTEM products must not be mixed with other manufacturers' products.

Only for commercial use.

Our technical data sheets / technical information and application instructions reflect the current level of knowledge in our company and the experience with our products. In each case, the new edition supersedes the previous technical information and renders it invalid. It is therefore necessary that you always have to hand the current code of practise. The latest version can be retrieved from the KEMPER SYSTEM Login section. When using our products, a detailed, object-related and qualified inspection is required in each individual case in order to determine whether the product and /or application technology in question meets the specific requirements and purposes. We are liable only for our products being free from faults, and this only if our relevant product has been used and applied according to the instructions in our technical data sheets. Correct application of our products therefore falls entirely within the scope of liability and responsibility of the user (contractor). Our products are sold exclusively on the bases of our conditions of sale and delivery.